PLUS PACK

For aluminum food contact articles – inside plain/outside plain (lid)

Plus Pack item no.	Description		Intended for:	
7610008900 0765510600	CONT.ALU.RECT.1010ML. CONT.ALU.RECT.550ML			
			Aqueous foods	Yes
Customer Reference	-		Acidic foods	No
Appearance	-		Alcoholic foods	Yes
Filling/Treatment			Fatty foods	Yes
Temperature	Max. 350 °C		Dry foods	Yes
Time	Up to 2 hours		Use in conventional oven	Yes
Storage after filling			Use in microwave	No
Temperature	-40 to +40 °C		Freezing	Yes
Combination of materials: (outside to inside)	Lubricant - aluminum foil - lubricant			
Restrictions:	No strong acidic or salty foodstuffs.			
Inventory storage	Max. 70 % RH	5-25 °C		

This item supplied by Plus Pack Group is intended to come into contact with the indicated foodstuffs and comply with the following EU Commission regulations and directives under the filling/treatment and storage conditions:

- Framework regulation (EC) 1935/2004 on materials and articles intended to come into contact with food with possible amendments.
- EN 602 Aluminium and aluminium alloys Wrought products Chemical composition of semifinished products used for the fabrication of articles for use in contact with food
- Directive (EC) 2023/2006 on good manufacturing practice for materials and articles intended to come into contact with food with possible amendments.
- Directive 94/62/EC on packaging and packaging waste (heavy metals) with possible amendments.
- Directive (EC) 1907/2006 REACH (Registration, Evaluation and Authorization of Chemicals) with possible amendments.
- o Directive 2003/89/EC concerning allergens with possible amendments.

All products are suitable for its intended use and have been tested for possible contamination and hazards (interactions) towards products and consumers. Migration tests have therefore been carried out. See Normpack certificates on www.pluspack.dk

Plus Pack will always assist in the choice of packaging, but the packer is ultimately responsible for choosing the right packaging for the product/process. The products must be tested until end shelf life time by correct packaging trials to avoid process problems – product smell, taste or visual deformation of the total end product.

Migration tests:

4 h at 100 °C in water 6 h at 60 °C in 95 % ethanol

Plus Pack AS Energivej 40 Postbox 151 DK - 5260 Odense S Tel: +45 6550 6000 ISO 9001 Certificeret www.pluspack.com admin.dk@pluspack.com Fax salg/logistik: Fax eksport: Fax økonomi/it: Fax direktion: +45 6550 6020 +45 6550 6040 +45 6550 6010 +45 6550 6051 DKK: EUR.: IBAN: CVR: Nordea 2206 0563 601124 Danske Bank 3574 3574 351367 DK20 3000 3574 351367 DK 37 75 40 13 No SML's present

Dual use additives that might be present	NA]			
Content of BPA	Inside	Outside			
	NA	NA			
International material recycling symbol:					
(alu)					
The statement is based on documentation from Plus Pack suppliers of raw materials and goods. The declaration is indicative and applies to the product when used during normal and foreseeable conditions consistent with referred temperature-, time- and contact constraints.					
• • • • • • • • • • • • • • • • • • •					

Odense, 2017-01-16

Quality & Process Manager